



CR-2003 CRICKET SCOREBOARD SPECIFICATIONS

The CR-2003 cricket scoreboard displays TOTAL, 1st INNS, BATSMAN, and LASTMAN up to three digits, OVERS up to 99 and WKTS to nine. The scoreboard also displays a umpire indicator.

PRODUCT SPECIFICATIONS

PRODUCT SAFETY APPROVAL:

ETL listed for outdoor use, tested to CSA standards for outdoor use, CE labeled for outdoor use.

DIMENSIONS:

Height 6'-9", Width 10'-0", Depth 6" (2058 mm, 3048 mm, 152 mm)

WEIGHT:

350 lb (159 kg)

POWER:

120 V AC, 5.0 A, 600 W
240 V AC, 2.5 A, 600 W

CONSTRUCTION:

Alcoa aluminum alloy 5052 for excellent corrosion resistance.

DIGITS:

All digits have a nominal size of 15" (381 mm) high, digits can be dimmed for night viewing. Umpire Indicator is a 4" diameter round cluster of LED's

CAPTIONS:

All captions are 8" (203 mm) high. All captions are white vinyl, applied directly to the display face.

CABINET COLOR:

More than 150 colors (from Martin Senour® paint book) are available at no additional cost.

OPERATING TEMPERATURES:

32 to 100 degrees Fahrenheit (0 to 38 degrees Celsius)
Console: 32 to 122 degrees Fahrenheit (0 to 50 degrees Celsius)

Notes: 1. Seven bar segments per digit; red (-11) or amber (-21) PanaView® LED digits.

CR-2003 PRODUCT SPECIFICATIONS (CONTINUED)

ALL SPORT® 5010 CONTROL CONSOLE:

Control console electronics are housed in a rugged aluminum case. Console has a 32-character liquid crystal prompting display to verify entries and recall information currently displayed. Case and sealed membrane keyboard make console face water-resistant. Console is capable of controlling other sports using keyboard inserts. A 20' (6096 mm) control cable and a 6' (1829 mm) power cord are supplied. The power cord plugs into a standard grounded 120 V AC outlet. Maximum power demand is 6 watts. All 230 V AC scoreboards use All Sport® 5020 control consoles.

CONTROL CABLE:

One-pair shielded control cable of 22 AWG minimum is required.

JUNCTION BOX:

A cover plate with mounted connector and standard 2" x 2" x 4" (51 mm, 51 mm, 102 mm) outlet box is provided. Connector mates with the connector from the control console.

SERVICE ACCESS:

Digit panels and electronics are serviced from the front of the scoreboard.

GENERAL INFORMATION:

Scoreboard provides scoring capability for two teams. 100% solid state electronics housed in an all aluminum cabinet. Scoreboard comes completely assembled. This scoreboard is shipped in one section and includes hardware to mount on two poles. Hardware for additional poles is available at additional cost. Specifications and pricing are subject to change without notice.

WARRANTY/SERVICE PLAN:

Exclusive Daktronics Gold® plan in the U.S. and Canada (see SP10093 for more information).

OPTIONS:

1. Durable carrying case for control console
2. 2.4 GHz spread spectrum radio control
3. Logo/sponsor panels
4. Electronic message display
5. Alternate caption colors available (see SL06409)
6. Protective netting
7. Protective screens for LED digits

FOR ADDITIONAL INFORMATION REFER TO:

1. Installation Layout Specification Drawing PENDING
2. Scoreboard Mounting Drawing #: 1091-R10A-55101
3. System Riser Diagram Drawing #: 1344-R01A-165779

For additional information on Daktronics scoring/timing products, call 605-697-4300 or 800-325-8766.

All Sport®, Gold® and PanaView® are trademarks of Daktronics, Inc. Martin Senour® is a registered trademark of its owner.

SL022908-07609 Page 2 of 2 Copyright © 2000-2008 Daktronics, Inc.

For faster service call the appropriate sales group toll-free:

800-DAKTRONICS (800-325-8766) General Sales
888-DAK SCORE (888-325-7267) High School/Park & Rec Sales
888-DAK SIGN (888-325-7446) Commercial Sales
800-558-9526 Business Communications Sales
888-DAK TIME (888-325-8463) College/University Sales
888-CHRONDEK (888-247-6633) Auto Racing Sports

